was was well as the second was well as the se

End of Result Set

Generate Collection Print

L2: Entry 1 of 1

File: DWPI

Mar 21, 2001

DERWENT-ACC-NO: 1999-527940

DERWENT-WEEK: 200117

COPYRIGHT 2002 DERWENT INFORMATION LTD

TITLE: Absorbent paper product useful as toilet paper, a paper napkin or a paper tissue

INVENTOR: HOEFT, B; ROUSSEL, G

PATENT-ASSIGNEE:

ASSIGNEE CODE FORT JAMES FRANCE JAME

PRIORITY-DATA: 1998FR-0002792 (March 6, 1998)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
EP 1084300 A1	March 21, 2001	F	000	D21H027/40
WO 9945205 A1	September 10, 1999	F	020	D21H027/40
FR 2775698 A1	September 10, 1999		000	D21H027/40

DESIGNATED-STATES: BE CH DE DK ES FI FR GB GR IE IT LI NL PT SE CA NO TR US AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE

APPLICATION-DATA:

PUB-NO	APPL-DATE	APPL-NO	DESCRIPTOR
EP 1084300A1	March 5, 1999	1999EP-0937958	
EP 1084300A1	March 5, 1999	1999WO-FR00504	
EP 1084300A1		WO 9945205	Based on
WO 9945205A1	March 5, 1999	1999WO-FR00504	
FR 2775698A1	March 6, 1998	1998FR-0002792	

INT-CL (IPC): $\underline{A47}$ K $\underline{10/16}$; $\underline{B31}$ F $\underline{1/07}$; $\underline{B32}$ B $\underline{29/00}$; $\underline{B32}$ B $\underline{31/00}$; $\underline{D21}$ H $\underline{27/32}$; $\underline{D21}$ H $\underline{27/40}$; $\underline{D21}$ H $\underline{27:38}$

ABSTRACTED-PUB-NO: WO 9945205A

BASIC-ABSTRACT:

NOVELTY - An absorbent paper product comprises external embossed layers which have a high inner protuberance density and which are bonded by adhesive to a central non-embossed layer.

DETAILED DESCRIPTION - An absorbent paper product of 36-105 g/m3 weight comprises external embossed layers which have relief patterns, consisting of more than 30 discrete protuberances per cm2 directed towards the interior of the structure, and which are joined by adhesive bonding of the protuberance tips to a central non-embossed layer. An INDEPENDENT CLAIM is also included for production of an absorbent paper product, comprising three layers of individual weight 12-35 (preferably 12-25) g/m2, by embossing two of the layers to form relief patterns of discrete protuberances, placing a non-embossed layer on the protuberances of one of the embossed layers, applying

adhesive onto the non-embossed layer, applying the other embossed layer such that the protuberances are aligned and pressing the layers to cause adhesive bonding.

USE - As toilet paper, a paper napkin or a paper tissue (claimed).

 $\ensuremath{\mathsf{ADVANTAGE}}$ - The product has a soft and thick feel and good crush resistance after winding.

DESCRIPTION OF DRAWING(S) - The drawing shows a cross-sectional view of a product of the invention.

Product 1

External embossed layers 2, 3

Central non-embossed layer 4

Protuberances 11, 33

Bonding points A1, A2

CHOSEN-DRAWING: Dwg.1/4

TITLE-TERMS: ABSORB PAPER PRODUCT USEFUL TOILET PAPER PAPER NAPKIN PAPER TISSUE

DERWENT-CLASS: F09 P72 P73

CPI-CODES: F05-A06A; F05-A06B;

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1999-155307 Non-CPI Secondary Accession Numbers: N1999-390982